

# SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### 1.1 Product identifier

Product name HYDROSTOP PART A  
Synonym(s) TAMSI HYDROSTOP PART A

### 1.2 Uses and uses advised against

Use(s) EPOXY RESIN SYSTEM TWO COMPONENT EPOXY SYSTEM WATER PROOFING

### 1.3 Details of the supplier of the product

Supplier name TAMSI INDUSTRIES PTY LTD  
Address Unit 48/8 Jullian Close, Banksmeadow, NSW, 2019, AUSTRALIA  
Telephone 02 9550 2822  
Fax N/A  
Email [info@tamsi.com.au](mailto:info@tamsi.com.au)

### 1.4 Emergency telephone number(s)

Emergency 02 9550 2822

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS classification(s) Skin Corrosion/Irritation: Category 2  
Skin Sensitisation: Category 1  
Serious Eye Damage / Eye Irritation: Category 2A  
Aquatic Toxicity (Chronic): Category 2

### 2.2 Label elements

Signal word WARNING

Pictogram(s)



Hazard statement(s)

H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.

Prevention statement(s)

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statement(s)

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P321 Specific treatment is advised - see first aid instructions.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P362 Take off contaminated clothing and wash before re-use.  
 P391 Collect spillage.

Storage statement(s)

None allocated.

Disposal statement(s)

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

No information provided.

### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
BISPHENOL-A-(EPICHLORHYDRIN), REACTION PRODUCT	25068-38-6	500-033-5	40 to 60%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder

### 4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

First aid facilities None allocated.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes and skin. May cause sensitisation by skin contact.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases (carbon/ nitrogen oxides, hydrocarbons) when heated to decomposition.

5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

3Z  
 3 Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, normal foam can be used.  
 Z Wear full fire kit and breathing apparatus. Contain spill and run-off.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

### 6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use.

### 7.3 Specific end use(s)

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

Exposure standards

No exposure standards have been entered for this product.

Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

PPE

Eye / Face	Wear splash-proof goggles.
Hands	Wear viton (R) or nitrile gloves.
Body	Wear coveralls. If spraying, with prolonged use, or if in confined areas, wear impervious coveralls.
Respiratory	Where an inhalation risk exists, wear a Type A (Organic vapour) respirator. If sanding dry product, wear a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear an Air-line respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	VISCOUS GREY LIQUID
Odour	SLIGHT ODOUR
Flammability	NON FLAMMABLE

9.1 Information on basic physical and chemical properties

Flash point	NOT RELEVANT
Boiling point	> 100°C
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Specific gravity	1.50
Solubility (water)	SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid) and alkalis (e.g. sodium hydroxide).

10.6 Hazardous decomposition products

May evolve toxic gases (carbon/ nitrogen oxides, hydrocarbons) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Information available for the ingredient(s):

Ingredient	Oral Toxicity (LD50)	Dermal Toxicity (LD50)	Inhalation Toxicity (LC50)
BISPHENOL-A-(EPICHLORHYDRIN), REACTION PRODUCT	2 - 19 g/kg (rat)	> 20 mL/kg (rabbit)	--

Skin	Contact may result in irritation, redness, rash and dermatitis.
Eye	Contact may result in irritation, lacrimation, pain and redness.
Sensitisation	Epoxy resins may cause allergic skin reactions. Insufficient data for classification as a respiratory sensitiser.
Mutagenicity	Not classified as a mutagen.
Carcinogenicity	Not classified as a carcinogen.
Reproductive	Not classified as a reproductive toxin.
STOT - single exposure	Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in dizziness, drowsiness and breathing difficulties.
STOT - repeated exposure	Not classified as causing organ damage from repeated exposure.
Aspiration	Not classified as causing aspiration.

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No information provided.

### 12.3 Bioaccumulative potential

No information provided.

### 12.4 Mobility in soil

No information provided.

### 12.5 Other adverse effects

No information provided.

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Waste disposal Mix components together (small amounts), absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer/supplier for additional information (if required). Prevent contamination of drains and waterways as environmental damage may result.

Legislation Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	3082	3082	3082
14.2 Proper Shipping Name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
14.3 Transport hazard class	9	9	9
14.4 Packing Group	III	III	III

### 14.5 Environmental hazards

No information provided.

### 14.6 Special precautions for user

Hazchem code 3Z  
 GTEPG 9C1  
 EMS F-A, S-F

Other information Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the Australian Dangerous Goods Code when transported by road or rail in;  
 (a) packagings;  
 (b) IBCs; or  
 (c) any other receptacle not exceeding 500 kg(L).  
 - Australian Special Provisions (SP AU01) - ADG Code 7th Ed.  
 Labels Required: MISCELLANEOUS.

---

## 15. REGULATORY INFORMATION

---

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule	Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).	
Classifications	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.  The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].	
Hazard codes	N Xi	Dangerous for the environment Irritant
Risk phrases	R36/38 R43 R51/53	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.
Safety phrases	S2 S28 S37/39 S61	Keep out of reach of children. After contact with skin, wash immediately with plenty of water. Wear suitable gloves and eye/face protection. Avoid release to the environment. Refer to special instructions/safety data sheets.
Inventory listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.	

---

## 16. OTHER INFORMATION

---

Additional information	<p>This product is used in conjunction with Hydrostop Part B. Please refer to the appropriate SDS before use.</p> <p><b>WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT:</b> If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (e.g. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.</p> <p><b>EPOXY RESINS:</b> Epoxy resins may contain low concentrations of glycidal ethers and/or epichlorohydrin, which are potential sensitising agents, both skin and respiratory. Epichlorohydrin is classified as probably carcinogenic to humans (IARC Group 2A).</p> <p><b>EPOXY - PHENOXY RESINS AND POLYURETHANES:</b> Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a full face air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered non toxic.</p> <p><b>PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:</b> The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.</p> <p><b>HEALTH EFFECTS FROM EXPOSURE:</b> It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.</p>
------------------------	--

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
	GHS	Globally Harmonized System
	GTEPG	Group Text Emergency Procedure Guide
	IARC	International Agency for Research on Cancer
	LC50	Lethal Concentration, 50% / Median Lethal Concentration
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m <sup>3</sup>	Milligrams per Cubic Metre
	OEL	Occupational Exposure Limit
	pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	SWA	Safe Work Australia
	TLV	Threshold Limit Value
	TWA	Time Weighted Average

Report status      This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by      Risk Management Technologies  
 5 Ventnor Ave, West Perth  
 Western Australia 6005  
 Phone: +61 8 9322 1711  
 Fax: +61 8 9322 1794  
 Email: info@rmt.com.au  
 Web: www.rmt.com.au

[ End of SDS ]